



# Lexmark XC4342

Color and performance

















#### Lexmark XC4342

The Lexmark XC4342 is designed for performance, security, and ease of use for mid-to-large workgroups at speeds up to 42 pages per minute\*. Single-pass two-sided scanning and a 7-inch (17.8 cm) tablet-like touchscreen make handling your tasks easy. Replacement cartridges with Unison™ Toner yield up to 25,000/14,200 black/color pages\*\* to keep you going.

## Robust, enduring quality

- Enjoy high-quality color output in a wide variety of environments—from back-office to retail to harsh manufacturing conditions.
- Intentionally engineered to last seven years or more with durable steel frames and long-life components.
- Unison™ Toner replacement cartridges yield up to 25,000/ 14,200 black/color pages\*\*.
- Make a statement with professional color

Enjoy the benefits of vibrant, professional-quality output allowing you to do more color printing in-house—saves time and money. Match corporate colors on marketing collateral and brand-sensitive text and graphics with PANTONE® calibration and Lexmark Named Color Replacement.



# Always easy. Always intuitive.

- Large, tablet-like, button-free touchscreens help you intuitively complete every task, from the basic to the complex.
- Get into the flow with standard access to built-in MFP

- workflow solutions like Scan Center, an easy-to-use app that simplifies routing to multiple destinations simultaneously.
- An Intelligent Storage Drive (ISD) is standard on this model, providing faster startup, faster data retrieval and more reliability.
- Plus, you can add other Lexmark or third-party partner solutions that meet your specific business needs.

### Secure by design

Lexmark security features help keep your information safe—in the document, on the device, over the network and at all points in between. Our comprehensive approach to product security is a design and engineering mandate across our entire product portfolio.

### Sustainability matters

- Designed for the circular economy.
- Automatic two-sided printing is standard, along with built-in energy-saving modes that help support ratings of EPEAT® Silver and ENERGY STAR® certified.
- The award-winning Lexmark Cartridge Collection Program (LCCP) and Lexmark Equipment Collection Program (LECP) minimize waste and support recycling (availability varies by country).

#### Power up with IoT

- Sophisticated, IoT-enabled printers are loaded with sensors that continuously monitor hundreds of data points.
- When you connect your device to Lexmark Cloud Services, you can optimize performance and uptime with additional features like predictive service and automatic supplies replenishment.

This is a Class A device according to international electromagnetic emissions standards (i.e. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/non-domestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.

<sup>\*</sup> Print speeds measured in accordance with ISO/IEC 24734 (ESAT). For more information see: www.lexmark.com/ISOspeeds.

<sup>\*\*</sup> Average yield based on approximately 5% print coverage. In demonstration of circular economy principles, genuine Lexmark supplies with Unison™ Toner may contain components recovered from the Lexmark Cartridge Collection Program (LCCP).

<sup>\*\*\*</sup> IPDS License and Bar Code License require an Intelligent Storage Drive.

#### Lexmark XC4342



- Multifunction product with 7-inch (17.8 1 cm) touch screen 24.44 x 18.85 x 20.9 in. 621 x 479 x 533 mm
- 2 550-Sheet tray with 100-sheet multipurpose feeder Dimensions included as part of base model
- 3 550-Sheet Trav 4.7 x 18.23 x 19 in. 119 x 463 x 483 mm
- 4 550-Sheet Tray 4.7 x 18.23 x 19 in. 119 x 463 x 483 mm

- 5 550-Sheet Tray 4.7 x 18.23 x 19 in. 119 x 463 x 483 mm
- 6 550-Sheet Tray 4.7 x 18.23 x 19 in. 119 x 463 x 483 mm
- Adjustable Stand 7 20.5 x 25.7 x 24.6 in. 521 x 653 x 625 mm
- Convenience Stapler LV 8 3.23 x 4.29 x 4.77 in.



Standard

Optional

P/N Hardware 47C9800 Lexmark XC4342 P/N Supplies Lexmark XC4342, 4352 Cyan 24B7515

14.2K Toner Cartridge 24B7516 Lexmark XC4342, 4352 Magenta 14.2K Toner Cartridge

Lexmark XC4342, 4352 Yellow 24B7517

14.2K Toner Cartridge 24B7518 Lexmark XC4342, 4352 Black 25K

Toner Cartridge 71C0W00 Lexmark CS/CX730, 735, C/ XC4342, C4352 170K Waste

Container

Lexmark CS/CX730, 735, C/ 71C0Z10 XC4342, C/XC4352 Black 150K

Imaging Unit

Lexmark CS/CX730, 735, C/ 71C0Z50 XC4342, C/XC4352 Color (CMY)

150K Imaging Unit

P/N **Paper Handling** 40C2100 550-Sheet Tray 47C4500 Convenience Stapler

P/N **Memory Options** 27X0400 500+ GB Hard Disk

57X0070 Removable Hard Disk Enclosure

57X9528 Intelligent Storage Device (ISD)

P/N **Application Solutions** 57X0300 Contact Authentication Device 57X0301 Contactless Authentication

Device IPDS License

82S1203 82S1204 Bar Code License P/N Connectivity

USB Cable (2-meter) 1021294 27X0823 MarkNet N8370 Wireless for

CS720, CS725, CX725

Lexmark MarkNet N8372 802.11 27X6410 a/b/g/n/ac Wireless Print Server

37X6350 Analog Fax Card English Keyboard Kit 57X7020 Surge Protective Device, SPD0001

110-120V

P/N **Furniture** 40C2300 Adjustable Stand

| <b>Product Specifications</b>                  | Lexmark XC4342   |
|--|--|
| Printing                                       |  |
| Display  | Lexmark e-Task 7-inch (17.8 cm) color touch screen   |
| Print Speed                                    | Up to: Black: 42 ppm <sup>1</sup> (Letter) / Color: 42 ppm <sup>1</sup> (Letter)   |
| Time to First Page                             | As fast as: Black: 6.4 seconds / Color: 7.0 seconds  |
| Print Resolution                               | Black: 1200 x 1200 dpi, 4800 CQ (2400 x 600 dpi) / Color: 4800 CQ (2400 x 600 dpi), 1200 x 1200 dpi  |
| Memory   | Standard: 2048 MB / Maximum: 2048 MB   |
| Hard Disk                                      | Intelligent Storage Drive included; Magnetic Hard Disk available   |
| Recommended Monthly Page Volume                | 1500 - 15000 pages <sup>2</sup>  |
| Maximum Monthly Duty Cycle                     | Up to: 120000 pages per month <sup>3</sup>   |
| Copying  |  |
| Copy Speed                                     | Up to: Black: 42 cpm <sup>1</sup> (Letter) / Color: 42 cpm <sup>1</sup> (Letter)   |
| Time to First Copy                             | As fast as: Black: 6.7 seconds / Color: 7.3 seconds  |
| Scanning                                       |  |
| Scanner Type / ADF Scan                        | Flatbed scanner with ADF / DADF (single pass Duplex)   |
| A4/Ltr Duplex Scan Speed                       | Up to: Black: 80 / 84 sides per minute / Color: 80 / 84 sides per minute   |
| A4/Ltr Simplex Scan Speed                      | Up to: Black: 40 / 42 sides per minute / Color: 40 / 42 sides per minute   |
| ADF Paper Input Capacity                       | Up to: 100 pages 20 lb or 75 gsm bond  |
| Supplies <sup>4</sup>                          |  |
| Laser Cartridge Yields                         | up to: 14,200 <sup>5</sup> -page Color (CMY) High Yield Cartridges / up to: 25,000 <sup>5</sup> -page Black Extra High Yield Cartridge   |
| Imaging Unit Estimated Yield                   | Up to: 150000 pages, based on 3 average letter/A4-size pages per print job and $\sim$ 5% coverage $^6$   |
| Cartridge(s) Shipping with Product             | 5,000 <sup>5</sup> -page (CMYK) Return Program Toner Cartridges <sup>5</sup>   |
| Paper Handling                                 |  |
| Included Paper Handling                        | 100-Sheet Multipurpose Feeder, Integrated Duplex, 300-Sheet Output Bin, 550-Sheet Input  |
| Optional Paper Handling                        | 550-Sheet Tray   |
| Paper Input Capacity                           | Up to: Standard: 650 pages 20 lb or 75 gsm bond / Maximum: 2850 pages 20 lb or 75 gsm bond   |
| Paper Output Capacity                          | Up to: Standard: 300 pages 20 lb or 75 gsm bond / Maximum: 300 pages 20 lb or 75 gsm bond  |
| Media Types Supported                          | Vinyl Labels, Banner Paper, Paper Labels, Card Stock, Plain Paper, Envelopes, Refer to the Paper & Specialty Media Guide   |
| Media Sizes Supported                          | A6, Oficio, 7 3/4 Envelope, 9 Envelope, JIS-B5, A4, Legal, A5, Letter, B5 Envelope, Statement, C5 Envelope, Executive, Universal, DL Envelope, Folio, 10 Envelope  |
| General Information <sup>7</sup>               |  |
| Standard Ports                                 | Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), Rear Hi-Speed USB Port Compatible with USB 2.0 Specification (Type A), USB 2.0 Specification Hi-Speed Certified (Type B), One Internal Card Slot |
| Optional Network Ports                         | Internal MarkNet N8370 802.11b/g/n/a Wireless, NFC   |
| Noise Level                                    | Operating: 52 dBA (Print) / 55 dBA (Copy) / 51 dBA (Scan)  |
| Specified Operating Environment                | Humidity: 8 to 80% Relative Humidity / Temperature: 10 to 32°C (50 to 90°F) / Altitude: 0 - 2896 Meters (9,500 Feet)   |
| Limited Warranty                               | See Statement of Limited Warranty: 1-Year Onsite Service, Next Business Day  |
| Size / Weight                                  | H x W x D: 24.44 x 18.85 x 20.9 in. / 85.98 lb.  |
| ENERGY STAR Typical Electricity<br>Consumption | TEC: 0.55 kilowatt-hours per week  |

All information is subject to change without notice. Lexmark is not liable for any errors or omissions.

1 Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.

<sup>2</sup> "Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. <sup>3</sup> "Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. <sup>4</sup> Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/regions for more details. <sup>5</sup> Average yield based on approximately 5% print coverage. <sup>6</sup> Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity. <sup>7</sup> Printers are sold subject to certain license/agreement conditions. See www.lexmark.com/printerlicense for details.

This is a Class A device according to international electromagnetic emissions standards (i.e. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/non-domestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.

© 2022 Lexmark. All rights reserved.

Lexmark, the Lexmark logo and Unison are trademarks of Lexmark International, Inc., registered in the United States and/or other countries.

Apple and AirPrint are trademarks of Apple Inc., registered in the U.S. and other countries and regions. MOPRIA®, the Mopria® Logo, and the Mopria Alliance TM word mark and logo are registered and/or unregistered trademarks and service marks of Mopria Alliance, Inc. in the United States and other countries. Unauthorized use is strictly prohibited. ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency. EPEAT is a trademark of the Green Electronics Council in the United States and other countries. PANTONE® is the property of Pantone LLC. All other trademarks are the property of their respective owners.

This product includes software developed by the OpenSSL Project for use in the Open SSL Toolkit (http://www.openssl.org/ (http://www.openssl.org/)).

